

7.H

From the INTERNATIONAL BUREAU

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

To:

Assistant Commissioner for Patents
United States Patent and Trademark
Office
Box PCT
Washington, D.C. 20231
ÉTATS-UNIS D'AMÉRIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 26 February 2000 (26.02.00)	
International application No. PCT/EP99/03953	Applicant's or agent's file reference pf980074
International filing date (day/month/year) 07 June 1999 (07.06.99)	Priority date (day/month/year) 08 June 1998 (08.06.98)
Applicant BICHOT, Guillaume et al	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:
07 January 2000 (07.01.00)

☐ in a notice effecting later election filed with the International Bureau on:

2. The election ☒ was
☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland	Authorized officer Martine Lee
Facsimile No.: (41-22) 740.14.35	Telephone No.: (41-22) 338.83.38



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 29/06, 12/28	A1	(11) International Publication Number: WO 99/65202 (43) International Publication Date: 16 December 1999 (16.12.99)									
<div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> <p>(21) International Application Number: PCT/EP99/03953</p> <p>(22) International Filing Date: 7 June 1999 (07.06.99)</p> <p>(30) Priority Data:</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 33%;">98401372.2</td> <td style="width: 33%;">8 June 1998 (08.06.98)</td> <td style="width: 33%;">EP</td> </tr> <tr> <td>98402384.6</td> <td>28 September 1998 (28.09.98)</td> <td>EP</td> </tr> <tr> <td>98402712.8</td> <td>30 October 1998 (30.10.98)</td> <td>EP</td> </tr> </table> <p>(71) Applicant (for all designated States except US): THOMSON MULTIMEDIA [FR/FR]; 46, quai Alphonse Le Gallo, F-92100 Boulogne-Billancourt (FR).</p> <p>(72) Inventors; and</p> <p>(75) Inventors/Applicants (for US only): BICHOT, Guillaume [FR/FR]; Thomson Multimedia, 46, quai Alphonse Le Gallo, F-92648 Boulogne Cedex (FR). STRAUB, Gilles [FR/FR]; Thomson Multimedia, 46, quai Alphonse Le Gallo, F-92648 Boulogne Cedex (FR). FANNECHERE, Nicolas [FR/FR]; Thomson Multimedia, 46 quai Alphonse Le Gallo, F-92648 Boulogne Cedex (FR).</p> <p>(74) Agent: KOHRS, Martin; Thomson Multimedia, 46, quai Alphonse Le Gallo, F-92648 Boulogne Cedex (FR).</p> </div> <div style="width: 48%;"> <p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published</p> <p><i>With international search report.</i></p> <p><i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p> </div> </div>			98401372.2	8 June 1998 (08.06.98)	EP	98402384.6	28 September 1998 (28.09.98)	EP	98402712.8	30 October 1998 (30.10.98)	EP
98401372.2	8 June 1998 (08.06.98)	EP									
98402384.6	28 September 1998 (28.09.98)	EP									
98402712.8	30 October 1998 (30.10.98)	EP									
<p>(54) Title: METHOD FOR TRANSMITTING ASYNCHRONOUS DATA IN A HOME NETWORK</p> <p>(57) Abstract</p> <p>The invention concerns a method for transmitting data in a home communication network. The network comprises a first device and a second device, wherein said first device includes means to produce a data packet and said second device includes means to use said data packet. The inventive method is characterised in that it comprises the steps of: opening a connection between said first device and said second device; having said second device allocate a message buffer to said connection, said second device communicating the message buffer size to said first device; having said first device transmit said data packet to said second device, wherein said data packet is split and sent as payload in messages, where the size of the payloads is smaller or equal to said message buffer size. The invention applies to home network communications.</p>											
<pre> sequenceDiagram participant Client participant FCM Client->>FCM: Open(IOID, message_buffer_size_client) Client->>FCM: 0, cid, message_size Client->>FCM: Write(cid, data, END) Client->>FCM: 0 Client->>FCM: Write(cid, data, START) Client->>FCM: 0 Client->>FCM: Write(cid, data, NEXT) FCM-->>Client: ok Client->>FCM: Write(cid, data, END) FCM-->>Client: ok Client->>FCM: Close(cid) </pre>											

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Method for transmitting asynchronous data in a home network

5 The specification 'Home Audio/Video interoperability architecture version 0.8', also called 'HAVi' architecture, was disclosed on May 15, 1998 on the WEB sites of at least the following companies: Sony, Philips, Toshiba, Sharp and Hitachi.

10 This specification describes the implementation of a home network comprising consumer electronics devices and computing devices, and compatible with the IEEE 1394 1995 serial bus and the IEC 61883 interface standards.

15 The HAVi specification version 0.8 describes in its sections 3.2 and 5.2 an inter-device communication system referred to as the 'Messaging System'. The Messaging System, sometimes also called the 'Message Passing System', is a software object (a 'software element' according to the HAVi terminology) present in some device types of the network. It possesses an application programmable interface, comprising a number of functions, which can be accessed by a software element to send a message to another software
20 element. When a software element calls a function of another software element of another device, the function called is mapped into a Messaging System message.

25 Messages use a predefined format which is described in section 3.2.1. of the HAVi document. A message contains two bytes defining the length of the message payload. The maximum length of a message is thus a little over 64 Kb: the maximum payload, to which the length of the header information is added.

30 The Messaging System of HAVi version 0.8 is well adapted for performing function calls and managing software element identifiers in the network. The inventors have recognized the following problem with the proposed architecture: when a sending software element sends a message to a receiving software element, the Messaging System does not take into account the memory capacity of the receiving software element. The receiving software element may encounter problems to process a huge amount of data if the
35 buffer allocated to the communication by the receiving software element is not adequate. In other words, the HAVi 0.8 document does not enable the receiving software element to control the amount of data it receives.

The object of the invention is a method for transmitting data in a home communication network comprising a first device and a second device, wherein said first device includes means to produce a data packet and said second device includes means to use said data packet, said method being characterised in that it comprises the steps of:

- opening a connection between said first device and said second device;

- having said second device allocate a message buffer to said connection, said second device communicating the message buffer size to said first device;

- having said first device transmit said data packet to said second device, wherein said data packet is split and sent as payload in messages, where the size of the payloads is smaller or equal to said message buffer size.

The receiving device specifies the size of its message buffer at the beginning of the transmission, and the sending device takes into account this value in order to maintain a limited payload size.

The word 'device' is not limited in its significance to a physical device. It comprises among others software objects, and in particular 'software elements' as defined by the HAVi 0.8 document.

According to a particular embodiment of the invention, said payloads have a first maximum length independent of said first and second devices and wherein a second maximum length dependent of said second device is constituted by said message buffer size, the shortest of said first and second maximum lengths being retained for sending messages to said second device.

The first maximum message size is that given by the specification in itself: for instance, HAVi 0.8 gives 64 kilobytes as the maximum message size. The second maximum message size is that defined within the connection, i.e. the message size of the receiving device. This message size has to be used only in connection with messages sent to that particular receiving device, and through the particular connection.

The invention thus solves a problem inherent to the network presented in the HAVi 0.8 document, while being compatible with this document, and in particular with the Messaging System.

Other characteristics and advantages of the invention will appear in the description of a non-limiting embodiment, described with the help of the enclosed figures, among which:

- figure 1 is a block diagram of a home network;
- 5 - figure 2 is a block diagram of a device in the home network of figure 1;
- figure 3 is a diagram of an example of the software objects and layers implemented in the device of figure 2;
- figure 4 is a diagram of message exchanges between an entity
10 producing a stream ('producer') and an entity receiving that stream ('consumer'), in the case the producer takes the initiative to send the stream;
- figure 5 is a diagram similar to figure 4, but in the case where the consumer takes the initiative to request a stream from the producer;
- figure 6 is a diagram of an exchange between two entities which
15 are both producer and consumer in the frame of a same connection.

The present description uses a terminology defined in the following document, to which one should also refer for further details about the home network architecture: 'The HAVi Architecture - Specification of the Home
20 Audio/Video interoperability (HAVi) Architecture' of May 11, 1998 Version 0.8 and publicly disclosed on May 15, 1998 on the WEB sites of at least the following companies: Sony, Philips, Toshiba, Sharp and Hitachi.

Figure 1 is a diagram of an example of a HAVi-compliant home
25 network comprising all four types of devices defined by the HAVi 0.8 specification. The home network comprises a communication bus, which is a IEEE 1394 1995 serial bus according to the present example. To this bus are connected a digital television, a digital receiver/decoder, a modem, a Digital Video Disc recorder/player (DVD) and a Videocassette Recorder (VCR). The
30 television receiver is a Full Audio/Video (FAV) device, which is the device type having the most functionalities according to the HAVi specification. In particular, the FAV type device has the capacity to execute HAVi runtime code. The television receiver can thus host the software to control the VCR, which in the present case is a Legacy device, i.e. a device having no HAVi functionality. The
35 Legacy device is connected directly to the Full Audio/Video device, since it does not have a bus connector or the necessary means to communicate on the bus. The digital decoder and the modem are Intermediate Audio/Video (IAV)

devices, which have many of the features of the FAV device, but not the capability to download software to control other devices. Such software may nevertheless be resident in an IAV device. Lastly, the DVD player is a Basic Audio/Video device, which does not have the means to run HAVi code, but has at least the capacity to connect to the communication bus and to communicate with a IAV or FAV device which runs the software interface between the HAVi environment and the Basic Audio/Video device's own environment.

Figure 2 is a block diagram of the television receiver's components related to its HAVi functionalities. The television receiver 1 contains a microprocessor 2, connected to a RAM memory 3 and a reprogrammable ROM memory 4 through an internal bus 7. The ROM is used to store the receiver's software elements and other code for managing the device's functionalities executed by the microprocessor. The television receiver also contains a connection 5 to the IEEE 1394 bus, the connection comprising a physical/link circuit (and the software required for the asynchronous transaction and bus management layers. The television receiver also comprises a connector 6 destined to control and exchange Audio/Video streams with a specific device, in this case the VCR of figure 1.

Figure 3 shows the organisation of software objects ('software elements' according to the HAVi terminology) in the television receiver, and more generally in a FAV-type device.

The television receiver hosts a number of applications and device control applications which interact with the following software elements through corresponding application programmable interfaces:

- a 1394 Communication Media Manager, which allows other software elements to perform asynchronous and isochronous communication over the IEEE 1394 bus,
- a Message Passing System, for exchanging messages with other software elements,
- an Event Manager for managing object state changes,
- a Stream Manager for managing Audio/Video data streams between functional components, such as a tuner and a recording device,
- a Registry, which keeps a list of local software elements and its identifiers and manages communication with distant registries,
- a Device Control Module Manager (DCMM), for loading or deleting Device Control Modules (DCM),
- a number of either resident or uploaded Device Control Modules.

The resident application of figure 3 is in the present case an Electronic Program Guide, while one of the Device Control Modules (DCMs) has been installed to control the VCR of figure 2, and another DCM has been
5 downloaded from the DVD player.

A device control module may control one or more Functional Control Modules, also called FCMs. An FCM is a software element which gives control over a specific function of a device through a well known function set, comprising groups of functions called Application Programmable Interfaces, or
10 APIs. In a digital television receiver/decoder, FCM APIs would typically be dedicated to the control of the tuner and the video/audio decoder.

According to the present embodiment, an Asynchronous Data API is defined. This API, or a part thereof, is to be included into the FCMs which require the capability of managing the transfer of asynchronous data streams
15 between a producer and a consumer.

The terms 'producer' and 'consumer' are used to designate the capability of a device or functional component to produce an asynchronous stream or to receive such a stream. Consumers and producers may be storage devices, but this is not necessarily so.

20 A digital stream demultiplexer demultiplexing service information is a producer. A recording device (for instance a memory, a magneto-optical disk, a hard disk or a digital video cassette recorder) can also be a producer. A piece of software generating or processing data may also be a producer.

Examples of consumers can also be given: a recording device
25 playing back information, a printer or a display device.

The notions of producer and consumer are not exclusive: some devices or functional components may have both functions within a same connection. An example of such a device is a modem connected to the public switched telephone network for accessing internet services. Seen from the
30 HAVi network, the modem can act as a consumer, i.e. by accepting data from a client application for transmission to an internet server, or it may act as a producer, when transferring data from the internet server to the client application. The client application is also both a producer and a consumer in this case.

35 The term 'asynchronous data stream' is used to make a distinction with the 'isochronous data streams', i.e. the audio and video streams handled by the Stream Manager defined by the HAVi document. Typically,

asynchronous data consists in data corresponding to a picture, a file or program code. An FCM implementing the functions explained in detail below will remain compatible with the Messaging System (as defined in the HAVi version 0.8 document) while correcting the deficiencies described in the introduction.

An FCM can manage one or more containers, a container being the general term to designate a consumer, a producer or an entity having both functions. If an FCM contains more than one container, then each container is identified by a unique label. Such a label is redundant if only one container is present, but can, according to a variant of the invention, nevertheless be implemented for system uniformity reasons.

The Asynchronous Data API is defined by the parameters and functions given below. Depending on whether an FCM is simply a consumer, a producer or both, the appropriate subsets of functions have to be implemented.

The term 'in' used in the function definitions defines parameters which are passed by the software element calling the function to the software element which receives the function call, while the term 'out' defines parameters sent back by the software element receiving the function call.

(a) The FileLoc parameter

This parameter indicates whether a message from a producer to a consumer is the first message, an intermediate message or the last message of a contiguous series of messages. The conditions of use of such series of messages will be explained be described later in relation with figures 4 to 6.

The parameter is defined as follows:

```
enum FileLoc { START, NEXT, MIDDLE};
```

(b) The Container parameter

It defines the characteristics of a container. For example, a container containing program files will be defined by its identifier ('ioid'), the names of files it contains, the file types and the sizes of the files.

The parameter is defined as follows:

```
struct Container {  
    ioid;  
    characteristics;  
}
```

(c) The OpenRead function

This function is implemented within an FCM which is only a producer. It is called by a consumer to request the transfer of an asynchronous stream from a container . It is defined as follows:

```
Status IoStream::OpenRead(  
    in any ioid,  
    in long message_buffer_size,  
    in OperationCode opCode,  
    out short cid  
)
```

'Status' is the type of the function return value.

The following parameters are used by the OpenRead function:

- ioid : This is the identifier of the container to be opened. It is not mandatory if the FCM which implements the function has only one container and will be ignored by that FCM if nevertheless present in the function call.

- message_buffer_size : This parameter indicates the maximum size of a message accepted by the consumer, excluding the messaging system overhead (i.e. the header and other data related to the messaging system layer). The producer will take into account that parameter to determine the length of its message payloads to the consumer. Preferably, the length of the payloads will be equal to the message buffer size of the consumer.

The message buffer size is either fixed or can be allocated dynamically by the calling software element on the basis of available memory resources when the connection is to be established. For the OpenRead function, the consumer takes the initiative to establish the connection, and so the message buffer size passed as a parameter in the OpenRead function is the size of the consumer message buffer.

- opCode : this parameter is a code the producer will use to send the stream to the consumer. This operation code identifies a function of the consumer which the producer has to call to forward a response to the client. This parameter is set by the consumer. The operation code uniquely identifies a function within a software element. In this case, it is the 'Write' function, as defined below. The unique address of a function in the network thus comprises the 'SEID' identifier and the operation code .

- cid : This parameter identifies a given connection between the producer and the consumer, since there may be more than one such connection. Its value is defined by the producer, and is different from all other such identifiers used by the same producer at a given moment, in order to uniquely identify each connection.

One of the following values is returned by the 'OpenRead' function call:

'0' if the call has been a success
'1' if the container identifier was not correct
'2' if the container could not be accessed. This can happen for example if too many read accesses are made over several connections at the same time.

(d) The OpenWrite function

This function is implemented in FCMs which are only consumers. It enables a producer to send an asynchronous stream to container of a consumer's FCM.

It is defined as follows:

```
Status IoStream::OpenWrite(  
    in any ioid,  
    out long message_buffer_size,  
  
    out short cid  
)
```

The following parameters are used, in addition to those which have already been defined:

- ioid,

message_buffer_size : indicates the maximum size of a message payload accepted by the consumer. The producer will take into account that parameter during the sending of the data and until a close request.

cid : This parameter identifies the connection. In the case of the OpenWrite function, it is the called FCM which defines the value of the cid parameter.

The function returns one of the following values:

'0' if the function call is successful,
'1' if the container identifier 'ioid' sent in the function call is not correct,
'2' if the container identified by the 'ioid' identifier cannot be
5 accessed.

(e) The Open function

This function is implemented in FCMs which act both as a consumer and as a producer in the frame of a same connection.

10 It enables a consumer/producer to receive/send an asynchronous stream from/to a container.

It is defined as follows:

```
Status IoStream::Open(  
    in any ioid,  
    in long message_buffer_size_client,  
    in OperationCode opCode,  
    out long message_buffer_size_FCM,  
    out short cid  
    )
```

20 The following parameters are used :

- ioid,

25 - message_buffer_size_client : This parameter indicates the maximum size of a message accepted by the client application which calls the FCM function. When the called FCM is a producer, it will take that parameter into account for the sending of the data to the consumer (i.e. the client application) and until a close request.

30 - message_buffer_size_FCM : This parameter indicates the maximum size of a message accepted by the FCM. When the clients application acts as a producer, it will take that parameter into account during the sending of the data to the consumer (i.e. the FCM) and until a close request.

35 - opCode : this parameter is the code which the FCM will use to send the asynchronous stream to the client application (which will act as a consumer). This operation code identifies a function of the client application API which the producer has to call to forward asynchronous data to the client. In

this case, it is the 'Write' function, as defined below. The unique address of a function in the network thus comprises the 'SEID' identifier and the operation code .

cid : This parameter identifies the connection. It is determined and delivered by the FCM.

The function returns one of the following values:

'0' if the function call is successful,

'1' if the container identifier 'oid' sent in the function call is not correct,

'2' if the container identified by the 'oid' identifier cannot be accessed.

(e) The Write function

The Write function is the function which has to be called by a producer to transfer data to a consumer. The producer has to wait for the return value of the Write function before calling this function a new.

This function is implemented at the consumer side. Its operation code is a well-known operation code when the FCM acts as a consumer, because the operational codes of the functions of the Asynchronous Data API are predetermined. In case a client application acts as a consumer, the operation code is sent to a producer as a parameter through the OpenRead or the Open function call by a consumer, because the Asynchronous Data API is not necessarily implemented by the client application. It is assumed here that the client application implements the Write function, although any proprietary function achieving similar results may be used.

The Write function is defined as follows:

IoStream::Write

Prototype

```
Status IoStream::Write (
                        in cid,
                        in FILELOC where,
                        in sequence <byte> data,
                        )
```

In addition to the parameters which have already been defined for the other functions, the following parameters are used by the Write function:

- where : This parameter informs the consumer that a message is the first, the last or an intermediate message among a series of messages for transferring a stream,

- data : This is the payload of the message, i.e. a part of the stream to be transferred.

The Write function returns one of the following return values:

'0' if the consumer requests further messages,

'1' if the consumer needs to inform the producer that it should abort the transfer.

(f) The Dir function

This function returns the list of identifiers of containers of an FCM. If the FCM manages only one default container, then the function need not be implemented.

According to a variant of the present embodiment, this function also returns other characteristics of each container (such as for example type of storage element, total space available, free space available, list of files etc...)

The function is defined as follows:

IoStream::Dir

Prototype

void IoStream::Dir(

out sequence <Container> list

)

The 'list' parameter is the list of containers managed by the FCM. As described above, a container is identified by its 'ioid' identifier. The list can be empty. This means that the FCM handles only one container.

(g) The 'Close' function

This function enables a consumer or a producer to close a previously opened connection, identified by the 'cid' parameter. The connection can only be closed by the client application which opened it.

A software element does not necessarily need to close a connection after a stream transfer has been achieved. It can keep the connection open and transfer further streams through that connection.

The function prototype is defined as follows:

```
Status IOStream::Close(  
                                in long cid  
5                                )
```

The only parameter is the 'cid' parameter, i.e. the identifier of this connection.

The receiving FCM acknowledges with one of the following status values:

- 10 0: The connection has been closed successfully,
- 1: The transmitted value of the 'cid' parameter is unknown.

Figure 4 illustrates the message flow between a consumer and a producer when the producer takes the initiative to send a stream.

15 A producer, for example the decoder of figure 1, requests its Messaging System to call the OpenWrite function of a consumer, for example the display of the digital television receiver of figure 1, in order to prepare the display to show a still picture which the decoder has demultiplexed and decompressed. The decoder has obtained the identifier of the Display FCM from its local Registry service, by requesting a list of all display devices in the network, and has decided to use the display of the digital television receiver. For this purpose, the Display FCM run by the Full Audio/Video device of the network of figure 1 comprises the required functions from the Application Programmable Interface defined above, i.e. the Open, Write and Close
20 functions.
25

More details about the Registry service are given in the French patent application FR 9805110 filed on April 23, 1998 in the name of THOMSON multimedia.

The consumer acknowledges the request for opening a connection
30 by returning the value '0', and passing the corresponding parameter values, i.e. the connection identifier 'cid', the size in bytes of the message buffer allocated to this connection and the operational code of the Write function, which is in principle not known by the producer. The producer will then proceed to transfer its data, adequately distributed over a number of messages in such a way that
35 none of the message payloads is longer than the specified message buffer size.

The producer will first make a Write function call in which the 'where' parameter has the value START, using the operational code previously received from the consumer. The 'START' value indicates that the message is the first message of a series of messages in which a piece of data greater than
5 the consumer's message buffer size is transferred. According to the preferred embodiment, the producer strives to use for each of its message payloads the maximum message length authorised by the consumer's message buffer size in order to reduce the overall number of messages required. In other words, the payload size is equal to the specified consumer buffer size if enough data
10 remains to be sent. If the buffer size specified by the consumer is greater than the limit defined by the HAVi document (i.e. 64 kilobytes in the version 0.8), then the payload size of the messages is limited to that size.

The producer will also include part of the data to be transferred into this first message. Subsequent messages will use the value 'NEXT' for the
15 'where' parameter, to indicate intermediate messages in the series of messages. The last message will use the 'END' value.

The producer will send messages only after having received a proper acknowledgement ('0' return value) for each Write function call it performs.

When all data has been transferred, the producer calls the Close
20 function to close the connection with the consumer.

Figure 5 illustrates the case where a consumer takes the initiative to open a connection, calling the 'OpenRead' function of a producer's FCM. Apart from the parameters which differ between the OpenRead function and the
25 OpenWrite function, the mechanism is similar to the one explained in connection with figure 4.

Figure 6 illustrates the case in which a consumer-producer client application initiates a full duplex connection with a consumer-producer FCM.
30 According to the present embodiment, the FCM manages a modem associated with a single container.

The client application opens the connection with the FCM providing as a parameter its maximum buffer size to handle incoming messages.. In response, the FCM initialises the modem, connects to a given server using
35 predetermined settings (phone number, connection name, password...) confirms the opening of the connection to the client application (by transmitting

the '0' status value) and transmits, among other parameters, its maximum message buffer size and the identifier of the connection (cid),.

The client's application then sends a first request (which according to the present example fits into one message payload to the FCM. The FCM
5 forwards the payload content through the modem access and acknowledges the transmission to the client application. The server processes the request and sends it back a response. The FCM receives the response flow and forwards it to the client application using several messages, distributing the response over the payloads of the messages according to the maximum buffer size of the
10 client application. The transfer of data continues until all data is transferred. The communication between the client application and the FCM continues according to a predefined protocol between the client application and the remote server.

According to this protocol, the client application then closes the
15 connection.

European patent application 98402384.6 filed on September 28, 1998 in the name of the Applicant and whose priority is claimed concerns an
20 internet access functional component module.

Claims

1. Method for transmitting data in a home communication network
5 comprising a first device and a second device, wherein said first device includes means to produce a data packet and said second device includes means to use said data packet, said method being characterised in that it comprises the steps of:

10 - opening a connection between said first device and said second device;

- having said second device allocate a message buffer to said connection, said second device communicating the message buffer size to said first device;

15 - having said first device transmit said data packet to said second device, wherein said data packet is split and sent as payload in messages, where the size of the payloads is smaller or equal to said message buffer size.

2. Method according to claim 1, characterised in that said payloads
20 have a first maximum length independent of said first and second devices and wherein a second maximum length dependent of said second device is constituted by said message buffer size, the shortest of said first and second maximum lengths being retained for sending messages to said second device.

3. Method according to claims 1 or 2, characterised in that said
25 connection is opened by said first device through a function call sent to said second device for writing data to said second device.

4. Method according to claims 1 or 2, characterised in that said
30 connection is opened by said second device through a function call sent to said first device for reading data from said first device.

5. Method according to one of the claims 1 to 4, characterised in that said first device comprises at least one data storage element for storing said data packet.

6. Method according to claim 5, characterised in that said device comprises more than one storage element, each of said storage elements being identified by an identifier.

5 7. Method according to one of the claims 1 to 6, characterised in that said second device comprises at least one data storage element for storing said data packet.

1 / 3







Fig. 2

2 / 3



3 / 3




Fig. 5




Fig. 6

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/03953

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04L29/06 H04L12/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04L H04N H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 604 166 A (SONY CORP) 29 June 1994 (1994-06-29) column 7, line 15 -column 8, line 56 column 11, line 38 -column 12, line 11 column 18, line 51 -column 19, line 26 figure 15	1-7
A	SONY PHILIPS HITACHI SHARP MATSUSHITA THOMSON TOSHIBA GRUNDIG: "Specification of the Home Audio/Video Interoperability Architecture" THE HAVI ARCHITECTURE, 11 May 1998 (1998-05-11), pages 25-29, XP002115566 the whole document	1-7

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

17 September 1999

Date of mailing of the international search report

02/11/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Lázaro López, M.L.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/03953

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0604166 A	29-06-1994	JP 6244849 A	02-09-1994
		CN 1092584 A	21-09-1994
		DE 69325978 D	16-09-1999
		US 5608730 A	04-03-1994
<hr/>			

REC'D 24 AUG 2000

WIPO

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference pf980074	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/EP99/03953	International filing date (day/month/year) 07/06/1999	Priority date (day/month/year) 08/06/1998
International Patent Classification (IPC) or national classification and IPC H04L29/06		
Applicant THOMSON MULTIMEDIA et al.		

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.


2. This REPORT consists of a total of 7 sheets, including this cover sheet.

- ☐ This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☒ Certain defects in the international application
- VIII ☒ Certain observations on the international application

Date of submission of the demand 07/01/2000	Date of completion of this report 22.08.2000
Name and mailing address of the international preliminary examining authority:  European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465	Authorized officer Chêne, X Telephone No. +49 89 2399 8266



**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/EP99/03953

I. Basis of the report

1. This report has been drawn on the basis of (*substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments.*):

Description, pages:

1-14 as originally filed

Claims, No.:

1-7 as originally filed

Drawings, sheets:

1/3-3/3 as originally filed

2. The amendments have resulted in the cancellation of:

- ☐ the description, pages:
☐ the claims, Nos.:
☐ the drawings, sheets:

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

4. Additional observations, if necessary:

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/EP99/03953

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Yes: Claims 1-7
	No: Claims
Inventive step (IS)	Yes: Claims
	No: Claims 1-7
Industrial applicability (IA)	Yes: Claims 1-7
	No: Claims

2. Citations and explanations

see separate sheet

VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted:

see separate sheet

VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

see separate sheet

Re Item V

Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Reference is made to the following documents cited in the International Search Report:
D1: EP-A-0 604 166 (SONY CORP), 29 June 1994 (1994-06-29),
D2: SONY PHILIPS HITACHI SHARP MATSUSHITA THOMSON TOSHIBA
GRUNDIG: 'Specification of the Home Audio/Video Interoperability
Architecture' THE HAVI ARCHITECTURE, 11 May 1998 (1998-05-11),
pages 25-29, XP002115566 .
2. The subject-matter of **independent claim 1 does not involve an inventive step** in the sense of Article 33(3) PCT for the following reasons:

Document D1, according to the main features of claim 1, discloses a method for transmitting data in a home communication network (column 1, lines 1-10) comprising a first device and a second device (column 7, lines 15-19: "*plurality of devices*"), wherein said first device includes means to produce a data packet (column 7, lines 42-51: "*a device [...] being adapted to transmit [...] a transmit signal [...] in which one frame [...] consists of an address field [...], a control field [...] and a data field*") and said second device includes means to use said data packet (column 8, lines 4-6), whereby said method comprises the step of having said first device transmit said data packet to said second device, wherein said data packet is split and sent as payload in messages (column 7, lines 52-54: "*transmitting data [...] in a manner divided into a plurality of frames*").

The subject-matter of claim 1 therefore differs from the method described in document D1 in that it adds the steps of

- opening a connection between said first device and said second device;
- having said second device allocate a message buffer to said connection, said second device communicating the message buffer size to said first device;
- and determining the size of the payload as smaller or equal to the message

buffer size from the second device.

The problem to be solved by the present invention may therefore be regarded as how to adapt the size of the payload to prevent the saturation of the second device with the transmitted data. This is a well known problem of flow control in telecommunication system.

The opening of a connection for the communication between two devices is well-known in the art. For example, the HAVI Architecture from which document D2 is extracted, already discloses such a communication method. Then, when the person skilled in the art encounters the problem of saturation of the second device, it is obvious for him to add a additional message in its message set to inform the emitter of the buffer size of the receiver, so that the emitter does not send messages greater than the message buffer size of the receiver. This is an obvious solution for flow control.

The skilled person, therefore, being aware of the disclosure of document D1 can apply common general knowledge of the art (for example, the HAVI Architecture and flow control mechanism) and arrive at the method of claim 1.

3. Furthermore, the subject-matter of **dependent claims 2-7** is, when interpreted with the help of the description, either derivable from the above cited documents or concerns simple embodiments without inventive merit in themselves.

Therefore, these claims **do not add inventive matter** to the claims upon which they are dependent.

In particular:

In **claim 2**, it is well-known for a person skilled in the art that a message usually have a maximum length, for example for implementation reason (in secured operative systems, the dynamic memory allocation is usually forbidden, so that all data are size limited). It is also the case in the HAVI 0.8 specification, as indicated by the Applicant in the description page 2, line 29. Then to retain the minimum size for the message size is obvious for a skilled person.

In **claims 3 and 4**, the way the connection is opened is already known from the HAVI specification.

In **claims 5-7**, the use of data storage element for storing data packet is a well-known knowledge in telecommunication systems (for example, hard-disc, magnetic tapes). Additionally, the additional features in the method **claims 5-7** relate to technical features defining an apparatus rather than step of a method. Namely, these claims define more clearly the first and second devices since they comprises one or more data storage element for storing the data packet. But no steps are defined, so that they cannot contribute to the inventive activity of the method.

Re Item VII

Certain defects in the international application

1. The independent claims do not **correctly** reflect the known prior art in the two-part form in accordance with Rule 6.3(b) PCT, with those features known in combination from the prior art being placed in the preamble (Rule 6.3(b)(i) PCT) and with the remaining features being included in the characterising part (Rule 6.3(b)(ii) PCT).
2. The document D1 reflecting the prior art is not introduced and briefly discussed in the description (Rule 5.1(a)(ii) PCT).
3. Reference signs, in parentheses, are missing after each features in the claims according to Rule 6.2(b) in order to facilitate the understanding of the claims.
4. Some clerical errors are present in the description:
 - page 4, lines 15-18 the opening parenthesis is not closed in this paragraph,
 - page 13, line 33: ".." instead of ".",
 - page 14, line 14: "*hen*" instead of "then".

The numbering of the paragraph from page 9 is not correct. The letter (e) is used for two consecutive paragraphs ("The Open function" and "the Write function").

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/EP99/03953

5. The reference to application numbers FR 9805110 (page 12, line 27) and EP 98402384.6 (page 14, line 18) is not allowed since these number are not accessible to the public. Note that the application EP 98402384.6 has been published with the publication number EP 0 964 558.
6. There are also some inconsistency in the description and the drawings:
 - page 4, line 28: there is no element in figure 3 with the name of "Message Passing System",
 - The description of the enumeration FileLoc (page 6, line 27) defines 3 values "START, NEXT, MIDDLE". But the value "END" (page 13, line 15) is also mentioned for the parameter where (of the Write function) which only accepts FileLoc value (page 10, lines 27-34).

Re Item VIII

Certain observations on the international application

The subject matter of **dependent claim 6** is not clearly defined in the sense of Article 6 PCT. The reference to "*said device*" is ambiguous, since there is not only one device but at least two devices - the first and the second ones - which play different roles.

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference pf980074	FOR FURTHER ACTION see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. PCT/EP 99/ 03953	International filing date (day/month/year) 07/06/1999	(Earliest) Priority Date (day/month/year) 08/06/1998
Applicant THOMSON MULTIMEDIA et al.		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 2 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

1. Basis of the report

- a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

- b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :

☐ contained in the international application in written form.

☐ filed together with the international application in computer readable form.

☐ furnished subsequently to this Authority in written form.

☐ furnished subsequently to this Authority in computer readable form.

☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ **Certain claims were found unsearchable** (See Box I).

3. ☐ **Unity of invention is lacking** (see Box II).

4. With regard to the **title**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established by this Authority to read as follows:

5. With regard to the **abstract**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No.

☒ as suggested by the applicant.

☐ because the applicant failed to suggest a figure.

☐ because this figure better characterizes the invention.

6

☐ None of the figures.

PATENT COOPERATION TREATY

KoH

From the
INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

PCT

To:

KOHRs, Martin
Thomson Multimedia
46, quai Alphonse Le Gallo
F-92648 Boulogne Cedex
FRANCE

NOTIFICATION OF TRANSMITTAL OF THE INTERNATIONAL PRELIMINARY EXAMINATION REPORT (PCT Rule 71.1)

Date of mailing
(day/month/year) 22.08.2000

Applicant's or agent's file reference
pf980074

IMPORTANT NOTIFICATION

International application No.
PCT/EP99/03953

International filing date (day/month/year)
07/06/1999

Priority date (day/month/year)
08/06/1998

Applicant
THOMSON MULTIMEDIA et al.

1. The applicant is hereby notified that this International Preliminary Examining Authority transmits herewith the international preliminary examination report and its annexes, if any, established on the international application.
2. A copy of the report and its annexes, if any, is being transmitted to the International Bureau for communication to all the elected Offices.
3. Where required by any of the elected Offices, the International Bureau will prepare an English translation of the report (but not of any annexes) and will transmit such translation to those Offices.

4. REMINDER

The applicant must enter the national phase before each elected Office by performing certain acts (filing translations and paying national fees) within 30 months from the priority date (or later in some Offices) (Article 39(1)) (see also the reminder sent by the International Bureau with Form PCT/IB/301).

Where a translation of the international application must be furnished to an elected Office, that translation must contain a translation of any annexes to the international preliminary examination report. It is the applicant's responsibility to prepare and furnish such translation directly to each elected Office concerned.

For further details on the applicable time limits and requirements of the elected Offices, see Volume II of the PCT Applicant's Guide.

Name and mailing address of the IPEA/



European Patent Office
D-80298 Munich
Tel. +49 89 2399 - 0 Tx: 523656 epmu d
Fax: +49 89 2399 - 4465

Authorized officer

Ahrens, R

Tel. +49 89 2399-8136

